


GF HT-PP pipe with single socket 40x2000mm

1150079

- Gray, monolayer, PP-material, according to EN 1451. The S class is S20.



Application information GF HT-PP pipe with single socket

Specification


- The system is made from monolayer polypropylene (PP) to ensure reliable performance in standard drainage applications.
- It is designed for non-pressurized soil and wastewater drainage in residential and commercial buildings.
- The system is fully compliant with EN 1451-1 for plastic soil and waste discharge and EN 13501 for fire classification.
- It achieves fire performance rating E according to EN 13501.
- The pipes are suitable for short-term exposure to high-temperature wastewater.
- The material provides high resistance to chemicals commonly found in domestic and commercial wastewater.
- The push-fit socket design with integrated sealing rings ensures quick installation and leak-tight connections.
- The system is available in nominal diameters ranging from DN 32 to DN 200.

Application

- Residential buildings
- Office buildings and conference facilities
- Schools, libraries, hospitals, and hotels
- Underground and above-ground house drainage
- Sustainable / green building projects
- Industrial facilities (short- and long-term use)
- Wastewater from kitchens, bathrooms, and household appliances (e.g. washing machines, dishwashers)

GF HT-PP pipe with single socket 40x2000mm

1150079



Status

Item Available From date

2026-02-01

Product code

Item no EAN	8698652042640
Item no GF	4801004001521
Item no GTIN	08698652042640
Item no VVS	186021200

Dimensions

Item Unit Height	40
Item Unit Length	2000
Item Unit Weight	0,508
Item Unit Width	40
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900551878
Packaging GTIN PL2	06414900172943
Packaging Height PL1	40
Packaging Height PL2	225
Packaging Length PL1	2000
Packaging Length PL2	2000
Packaging Quantity PL1	1
Packaging Quantity PL2	10
Packaging Type PL1	Piece
Packaging Type PL2	Bag
Packaging Volume PL1	0,0032
Packaging Volume PL2	0,0405
Packaging Weight PL1	0,508
Packaging Weight PL2	5,08

Packaging Width PL1	40
Packaging Width PL2	90
Measurements	
Wall thickness_s	20
Z Measurement d	50,3
Z Measurement d1	40
Z Measurement e	1,8
Z Measurement L1	45

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com