


GF HT-PP pipe with single socket S20 160x1000mm

1150115

- Gray, monolayer, PP-material, according to EN 1451. The S class is S20.



Application information GF HT-PP pipe with single socket

Specification


- The system is made from monolayer polypropylene (PP) to ensure reliable performance in standard drainage applications.
- It is designed for non-pressurized soil and wastewater drainage in residential and commercial buildings.
- The system is fully compliant with EN 1451-1 for plastic soil and waste discharge and EN 13501 for fire classification.
- It achieves fire performance rating E according to EN 13501.
- The pipes are suitable for short-term exposure to high-temperature wastewater.
- The material provides high resistance to chemicals commonly found in domestic and commercial wastewater.
- The push-fit socket design with integrated sealing rings ensures quick installation and leak-tight connections.
- The system is available in nominal diameters ranging from DN 32 to DN 200.

Application

- Residential buildings
- Office buildings and conference facilities
- Schools, libraries, hospitals, and hotels
- Underground and above-ground house drainage
- Sustainable / green building projects
- Industrial facilities (short- and long-term use)
- Wastewater from kitchens, bathrooms, and household appliances (e.g. washing machines, dishwashers)

GF HT-PP pipe with single socket S20 160x1000mm

1150115

**Status**

Item Available From date

2026-02-01

Product code

Item no EAN 8698652031644

Item no GF 4801016006321

Item no GTIN 08698652031644

Item no VVS 186029100

Dimensions

Item Unit Height 160

Item Unit Length 1000

Item Unit Weight 2,413

Item Unit Width 160

Item_UOM pce

Packaging

Packaging GTIN PL1 06414900230803

Packaging Height PL1 165

Packaging Length PL1 1005

Packaging Quantity PL1 1

Packaging Type PL1 Piece

Packaging Volume PL1 0,027361125

Packaging Weight PL1 2,513

Packaging Width PL1 165

Measurements

Wall thickness_s 20

Z Measurement d 176,5

Z Measurement d1 160

Z Measurement e 3,9

Z Measurement L1 75

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com