


GF JRG lockable union, lead-free DN15

1155862

- Description: to 6320, 6325, 9910, 9920, with flat gasket
- Temperature: max. 90°C
- Nominal pressure: PN10
- Material: brass lead-free
- Connection: female thread



Application information GF JRG lockable union, lead-free

Specification


- Wide product range
- Gunmetal body

Application

Potable water installations

GF JRG lockable union, lead-free DN15

1155862



Measurements

Cylindric thread G2	3/4
Female thread Rp1	1/2
LENGTH_L	58
Z Measurement d	15
Z	47

Product code

Item no EAN	7613263112453
Item no GF	350887712
Item no GTIN	07613263112453

Dimensions

Item Unit Height	30
Item Unit Length	64
Item Unit Weight	0,158
Item Unit Width	34
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900455701
Packaging GTIN PL2	06414900455718
Packaging Height PL1	30
Packaging Height PL2	120
Packaging Length PL1	64
Packaging Length PL2	180
Packaging Quantity PL1	1
Packaging Quantity PL2	10
Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box
Packaging Volume PL1	0,00006528

Packaging Volume PL2	0,002808
Packaging Weight PL1	0,175
Packaging Weight PL2	1,85
Packaging Width PL1	34
Packaging Width PL2	130

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com