


## GF JRG lockable union, lead-free DN20

**1155864**

- Description: to 6320, 6325, 9910, 9920, with flat gasket
- Temperature: max. 90°C
- Nominal pressure: PN10
- Material: brass lead-free
- Connection: female thread



### Application information GF JRG lockable union, lead-free

#### Specification


- Wide product range
- Gunmetal body

#### Application

Potable water installations

## GF JRG lockable union, lead-free DN20

1155864



### Product code

Item no EAN	7613263112446
Item no GF	350887912
Item no GTIN	07613263112446

### Dimensions

Item Unit Height	37
Item Unit Length	69
Item Unit Weight	0,244
Item Unit Width	40
Item_UOM	pce

### Packaging

Packaging GTIN PL1	06414900455725
Packaging GTIN PL2	06414900455732
Packaging Height PL1	37
Packaging Height PL2	120
Packaging Length PL1	69
Packaging Length PL2	180
Packaging Quantity PL1	1
Packaging Quantity PL2	10
Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box
Packaging Volume PL1	0,00010212
Packaging Volume PL2	0,002808
Packaging Weight PL1	0,26
Packaging Weight PL2	2,75
Packaging Width PL1	40
Packaging Width PL2	130

### Measurements

## Documents

Page with all documents



### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)