


GF HT-PP white socket 50mm

1184631

- White, PP-material, according to EN 1451



Application information GF HT-PP white socket

Specification


- The system is made from monolayer polypropylene (PP) to ensure reliable performance in standard drainage applications.
- It is designed for non-pressurized soil and wastewater drainage in residential and commercial buildings.
- The system is fully compliant with EN 1451-1 for plastic soil and waste discharge and EN 13501 for fire classification.
- It achieves fire performance rating E according to EN 13501.
- The pipes are suitable for short-term exposure to high-temperature wastewater.
- The material provides high resistance to chemicals commonly found in domestic and commercial wastewater.
- The push-fit socket design with integrated sealing rings ensures quick installation and leak-tight connections.
- The system is available in nominal diameters ranging from DN 32 to DN 200.

Application

- Residential buildings
- Office buildings and conference facilities
- Schools, libraries, hospitals, and hotels
- Underground and above-ground house drainage
- Sustainable / green building projects
- Industrial facilities (short- and long-term use)
- Wastewater from kitchens, bathrooms, and household appliances (e.g. washing machines, dishwashers)

GF HT-PP white socket 50mm

1184631



Status

Item Available From date

2026-02-01

Product code

Item no EAN	6414900085014
Item no GF	4900505000121
Item no GTIN	06414900085014
Item no VVS	186553350

Dimensions

Item Unit Height	92
Item Unit Length	64
Item Unit Weight	0,059
Item Unit Width	64
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900085595
Packaging Height PL1	400
Packaging Length PL1	800
Packaging Quantity PL1	400
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,192
Packaging Weight PL1	25,16
Packaging Width PL1	600

Measurements

Z Measurement d	50,5
Z measurement m	43,5
z1	3

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com